

4.2 50 - 52 MHz BANDPLAN

Frequency	Maximum Bandwidth	Mode	Usage
50000	500 Hz	Telegraphy (a)	50.000 - 50.080 Beacons
50100			50.090 Telegraphy center of activity
50100	2700 Hz	Telegraphy SSB MGM	50.100 - 50.130 Intercontinental Telegraphy/SSB
			50.110 DX Calling (c)
			50.150 SSB Center of activity
			50.185 Crossband activity center
			50.210 - 50.250 Meteor Scatter (MGM)
			50.230 Meteor Scatter (MGM) calling frequency
			50.285 PSK31 center of activity
	50.400 +/- 500Hz WSPR Beacons		
50500	12 kHz	All modes	50.510 SSTV (AFSK)
50.500			50.520-50.540 Simplex FM Internet Voice Gateways
			50.550 FAX working frequency
			50.600 RTTY (FSK)
			50.620 - 50.750 Digital communications
			50.630 DV calling
			51.210 - 51.390 FM/DV Repeater Inputs, 20 kHz spacing (e)
	51.410 - 51.590 FM/DV Simplex (f)		
	51.510 FM calling frequency		
52.000			51.810 - 51.990 FM repeaters output channels, 20 kHz spacing (e)

DV = Digital Voice

NOTES ON THE 50 - 52 MHz BANDPLAN

1. IARU REGION 1 BANDPLAN

This bandplan, first adopted at the IARU Region 1 Conference in Torremolinos (1990) and revised at the 1996 Tel Aviv conference and the 2002 San Marino Conference, is recommended for use in those countries in the European part of Region 1 which allow amateurs to operate in this part of the radio spectrum. In many countries in the African part of Region 1 (see footnotes accompanying the ITU frequency allocation table) the 50 - 54 MHz band is allocated to the Amateur Service on a primary basis, and in some cases, like for instance in South Africa, an adaptation of the Region 2 bandplan is used.

1.1. Footnotes

- a. Telegraphy is permitted over the whole band; Telegraphy exclusive between 50.000 - 50.100 MHz.

2. USAGE

The following notes are referring to the Usage column in the bandplan. As already set out in the introduction to section 3, in the right amateur spirit operators should take notice of these agreements which are made for operating convenience, but no right to reserved frequencies can be derived from a mention in the Usage column or from the following notes.

2.1. Footnotes

- c. The intercontinental DX calling frequency 50.110 MHz should not be used for calling within the European part of Region 1 at any time.
- d. Channelized equipment: On this band the FM channel spacing is 20/10 kHz.
- e. For the specification of FM telephony see section 8.2
- f. This segment is for simplex use only with no Digital Voice gateways permitted. Embedded data traffic is allowed along with Digital Voice. DV users should check that the channel is not in use by other modes
- g. Refer to Beacons Chapter for coordination of beacons in the beacon sub-band

For the numbering of FM telephony channels see 4.1

In those countries within the European part of IARU Region 1 where it is allowed to set up FM repeaters on 50 MHz, the indicated channels are recommended in order to establish a commonality.

In those countries where the National Authorities do not permit repeaters to operate with output frequencies above 51 MHz, repeater output frequencies may be 500 kHz below the repeater input frequencies. (Tel Aviv 1996)

4.3 70.0 - 70.5 MHz BANDPLAN (Davos 2005)

Frequency (MHz)	maximum Bandwidth	MODE	Usage
70.000 70.050	500Hz	TELEGRAPHY MGM	Beacons 70.030 Personal WSPR beacons
70.050 70.250	2700Hz	TELEGRAPHY SSB MGM	70.150 MS calling 70.185 Crossband center of activity 70.200 Telegraphy/SSB calling
70.250 70.294	12kHz	AM / FM a)	70.260 AM/FM calling
70.294 70.500	12kHz	FM CHANNELS, 12.5 kHz spacing	70.3000 RTTY/FAX 70.3125 Packet radio 70.3250 Packet radio 70.4500 FM calling 70.4625 70.4750 70.4875 Packet radio

NOTES ON THE 70 MHz BANDPLAN

- a) No MGM traffic between 70.250 and 70.294 MHz.
- b) Refer to Beacons Chapter for coordination of beacons Section 11

4.4 144 - 146 MHz BANDPLAN

Frequency (MHz)	Maximum Bandwidth (-6dB)	MODE	USAGE
144.000	500Hz	Telegraphy(a) EME	144.050 Telegraphy calling
144.110			144.100 Random MS(m)
144.110	500Hz	Telegraphy MGM	144.110–144.160 EME MGM
144.150			144.138 PSK31 center of activity
144.150	2700Hz	Telegraphy, SSB, MGM	144.160-144.180 alternative MGM allocation
144.180			144.170 alternative MGM calling frequency
144.180	2700Hz	Telegraphy & SSB	144.195-144.205 Random MS SSB (m)
144.360			144.300 SSB calling
144.360	2700Hz	Telegraphy, SSB, MGM	144.370 FSK441 Random calling(m)
144.399			
144.400	500Hz	Telegraphy MGM	Beacons exclusive(b)
144.491			144.4905 +/-500Hz WSPR Beacons
144.500	20kHz	All mode (f)	144.500 SSTV calling
144.794			144.525 ATV SSB talk back
144.794	12kHz	MGM (h)	144.600 RTTY calling(n)
144.990			144.630-144.660 Linear Transponder OUT
			144.660-144.690 Linear Transponder IN
			144.700 FAX calling
			144.750 ATV talk back
			144.800 APRS

144.994 145.194	12kHz	FM / Digital voice	Repeater Input exclusive (c)
145194 145.206	12kHz	FM / Digital voice (i)	Space communication (p)
145.206 145.5935	12kHz	FM / Digital voice (i)	145.2375 FM Internet Voice Gateway 145.2875 FM Internet Voice Gateways 145.300 RTTY local 145.3375 FM Internet Voice Gateway 145.375 digital voice calling 145.500 (mobile) calling
145.594 145.7935 145.794	12kHz	FM / Digital voice	Repeater Output exclusive (c,d)
145.806 145.806	12kHz	FM / Digital voice (i)	Space communication (p)
145.806 146.000	12kHz	ALL MODE (e)	Satellite exclusive

NOTES ON THE 144 - 146 MHz BANDPLAN

1. IARU REGION 1 BANDPLAN

The following notes are part of the officially adopted IARU Region 1 bandplan, and all member societies should strongly promote adherence to the recommendations made in these notes.

1.1. General

- i. In Europe no input or output channels of telephony repeaters shall be allowed to operate between 144.000 and 144.794 MHz.
- ii. Except in the part of the band allocated to the Amateur Satellite Service and the linear transponders it is not allowed to use input- or output frequencies in the 145 MHz band for repeaters with in- or output in other amateur bands (Miskolc-Tapolca 1978, San Marino 2002).
- iii. No packet-radio networks will be set up in the 145 MHz band (revised Lillehammer 1999)
It is recognised that in some parts of Region 1 the introduction of packet-radio may require the use of access frequencies in the 144 - 146 MHz band for a limited time (Düsseldorf 1989).

Note. The parts of Region 1 meant are those parts with low amateur population and/or those at the periphery of the Region, where exceptions can be tolerated as these do not harm the orderly use of the band in the parts of Region 1 where there is a greater pressure on the available spectrum space. In the latter part of the Region the second paragraph of the footnote should never be used to justify ignoring the first part for a considerable time.

1.2. Footnotes

- a. Telegraphy is permitted over the whole band, but preferably not in the beacon band; Telegraphy exclusive between 144.000 - 144.110 MHz.
- b. Refer to Beacons Chapter for coordination of beacons in the beacon sub-band Section 11
- c. For technical standards on FM and repeaters see section 8

If there is a real need for more repeater channels (see section 10), it is recommended that Societies or Repeater Groups consider setting up a repeater system on the higher frequency band(s).

Further to this subject the following recommendation was adopted in De Haan, 1993:

For FM repeater and simplex operation in the 144 to 146 MHz band IARU Region 1 will change to a genuine 12.5 kHz channel spacing system.

Furthermore in Tel Aviv, 1996 it was decided that societies shall promote the use of the 12.5 kHz channel spacing standard for FM channels in order to effectively implement the 12.5 kHz system .

For the numbering of FM telephony channels, see annex 2 to this section.

- d. Established simplex frequencies on repeater output channels may be retained.
- e. In view of the important public relations aspect of amateur satellite activities, it was decided at the IARU Region 1 Conference in Miskolc-Tapolca (1978) that:
 - i) AMSAT will be allowed to use the band 145.8 - 146.0 MHz for amateur satellite activity.

This decision was re-confirmed at the IARU Region 1 Conference in Brighton (1981).
 - iii) see also footnote p
- f. No unmanned stations shall use the all-mode segment, except for linear transponders and ARDF beacons. (Tel Aviv 1996, San Marino 2002)
- g. Attention is drawn to section 1.1. point iii of these Bandplan notes!
- h. Network stations shall only operate in the part of the 145 MHz band allocated to Digital Communications and will be permitted only for a limited time. Such network stations should also have access ports on other VHF/UHF or Microwave bands and should not use the 145 MHz band to forward traffic to other network stations. In view of the time limitation the set-up of new network stations is not encouraged (De Haan, 1993).

Unmanned packet radio stations are only allowed in the segment 144.800 - 144.990 MHz. Outside of this segment the signal level produced by those stations shall be not larger than 60 dB below the carrier level (measured in a 12 kHz bandwidth). Any other unmanned packet radio and digital access points must cease operation not later than 31 December 1997. (Tel Aviv 1996).

- i. This segment is for simplex use only with no Digital Voice gateways. Embedded data traffic is allowed along with digital voice. Digital Voice users should check that the channel is not in use by FM

2. **USAGE**

The following notes are referring to the Usage column in the bandplan. As already set out in the introduction to section IIc, in the right amateur spirit operators should take notice of these agreements which are made for operating convenience, but no right to reserved frequencies can be derived from a mention in the Usage column or from the following notes.

EME activity using MGM is commonly practised between 144.110-144.160MHz

2.1. Footnotes

- m. See procedures set out in section 7.4
- n. Publicity should be given to the usage of frequencies around 144.600 MHz by RTTY stations, in order to keep these frequencies clear from other traffic and to avoid interference with those RTTY stations.
- p. For FM voice communications with special stations like manned spacecraft it is recommended to use 145.200 MHz for simplex operation or 145.200/145.800 MHz for split-channel operation (Vienna 1995/Tel Aviv 1996).
- q. It is recognised that in the IARU Region 1 rules for the Championships in Amateur Radio Direction Finding (ARDF) competitions, the frequencies for the unmanned beacons are in the segment 144.500 – 144.900 MHz. These beacons run low power and are on the air only during ARDF events. (Davos 2005)

4.5 430 - 440 MHz BANDPLAN

Frequency MHz	Maximum Bandwidth	MODE	USAGE	
430.000	20kHz	ALL MODES	430.025 - 430.375	FM repeater output-channel freqs (F/PA/ON), 12,5 kHz spacing, 1.6 MHz shift (f)
SUB-REGIONAL (national bandplanning) (d)			430.400 - 430.575	Digital communication link channels (g) (j)
			430.600 - 430.925	Digital communications repeater channels (g) (j) (l)
			430.925 - 431.025	Multi mode channels (j) (k) (l)
			431.050 - 431.825	Repeater input channel freqs (HB/DL/OE), 25 kHz spacing, 7.6 MHz shift (f)
			431.625 - 431.975	Repeater input channel freqs (F/PA/ON), 12.5 kHz spacing, 1.6 MHz shift
431.975				
432.000	500Hz	Telegraphy (a)		EME
432.025	500Hz	Telegraphy (a) MGM	432.050	Telegraphy centre of activity
432.100			432.088	PSK31 centre of activity
432.100	2700Hz	Telegraphy SSB MGM	432.200	SSB centre of activity
432.400			432.350	Microwave talkback centre of activity
432.400			432.370	FSK441 random calling
432.400	500Hz	Telegraphy, MGM		Beacons exclusive (b)
432.490				

Frequency MHz	Maximum Bandwidth	MODE	USAGE	
432.500	12kHz	ALL MODES	432.500	NEW APRS FREQUENCY
432.500-432.600			LINEAR TRANSPONDER IN(e)	
432.600			RTTY (ASK/PSK)	
432.700			FAX (ASK)	
432.600-432.800			LINEAR TRANSPONDER OUT (e)	
432.975				REPEATER INPUT REGION 1 STANDARD, 25 kHz spacing, 2 MHz shift (Channel freq 432.600 - 432.975MHz) In the UK repeater OUTPUT channels.
433.000	12 kHz	FM Digital voice Repeater (p)		REPEATER INPUT REGION 1 STANDARD, 25 kHz spacing, 1.6 MHz shift (Channel freq 433.000--433.375 MHz) I
433.375				
433.400	12 kHz	FM Digital voice (f) (o)	433.400	SSTV(FM/AFSK)
433.575			433.450 433.500	digital voice calling (Mobile) FM calling
433.600				SIMPLEX CHANNELS, 25 kHz spacing, (Channel freq 433.400 -- 433.575 MHz)
433.600	20kHz	ALL MODES	433.600	RTTY (AFSK/FM)
			433.625 - 433.775	Digital communications channels (g) (h) (i)
			433.700	FAX channel (FM/AFSK)
434.000			434.000	Centre frequency of digital experiments as defined on note (m)
434.400	12kHz (c)	ALL MODES ATV (c)	434.450 -	Digital communications channels
434.594			434.575	(by exception !!) (i)

Frequency MHz	Maximum Bandwidth	MODE	USAGE	
434.594 ATV (c) & FM	12kHz (c)	ALL MODES		REPEATER OUTPUT (region 1 system), 25 kHz spacing, 1.6 MHz shift, (Channel freq 434.600 -- 434.975 MHz) In the UK repeater INPUT channels
434.981 435.000	20kHz (c)	Satellite service & ATV (c)		
438.000 438.000	20kHz (c)	ALL MODES	438.025 - 438.175 438.200 - 438.525 438.550 - 438.625 438.650 - 439.425 439.800 -- 439.975 439,9875	Digital communications channel frequency (g) Digital communications repeater channels (g) (j) (l) Multi-mode (j) (k) (l) Repeater output channels (HB/DL/OE), 25 kHz spacing, 7.6 MHz shift, (f) (p) Digital communications link channels (g) (j) POCSAG centre
440.000				

NOTES ON THE 430 - 440 MHz BANDPLAN

1.IARU REGION 1 430-440MHz BANDPLAN

The following notes are part of the officially adopted IARU Region 1 bandplan, and all member societies should strongly promote adherence to the recommendations made in these notes.

1.1. General

- i. In Europe no input or output channels of telephony repeaters shall be allowed to operate between 432 and 433 MHz.(From 1-1-2004 those frequencies are between 432.000 and 432.600 MHz)
- iii. FM telephony channels and Repeaters are specified in chapter 8.8.4

1.2. Footnotes

- a. Telegraphy is permitted over the whole narrow-band DX part of the band; Telegraphy exclusive between 432.000 - 432.100 MH. PSK31, however, can be used as well in this segment
- b. Refer to Beacons Chapter for coordination of beacons in the beacon sub-band
See Section **Fehler! Verweisquelle konnte nicht gefunden werden.**
- c.
 - i. ATV operators should be encouraged to use the microwave allocations where available, but may continue to use the 430 MHz band where permitted by the licensing authority. In case of interference between ATV and the Amateur Satellite Service ,the Satellite Service should have priority.
 - ii. ATV transmissions in the 435 MHz band should take place in the segment 434.000 - 440.000 MHz. The video carrier should be below 434.500 MHz or above 438.500 MHz. National societies should provide guidance to their members on the exact frequencies to be used, with due consideration of the interests of other users. (Noordwijkerhout 1987)
- d) The words "Sub-regional (national) bandplanning" appearing in IARU Region 1 VHF/UHF/Microwave bandplans mean the following:

In bands and sub-bands not available throughout Region 1, band-planning should be coordinated on a sub-regional basis between the countries where those bands and sub-bands are allocated to the Amateur Service. The words "national bandplanning" refer to bands/segments which are available only in a single country (such as the 70 MHz band allocation), or only in a few widely separated countries.(Torremolinos 1990)
- e) At the IARU Region 1 Conference in Torremolinos (1990) the output band for linear transponders was extended from 432.700 to 432.800 MHz under the following condition:

The established use of 432.600 MHz for RTTY (ASK/PSK) and 432.700 MHz for FAX should be respected when installing linear transponders which use this allocation.
- f). This segment is for simplex use only with no Digital Voice gateways. Embedded data traffic is allowed along with digital voice. Digital Voice users should check that the channel is not in use by other modes

2. USAGE

The following notes are referring to the Usage column in the bandplan. As already set out in the introduction to section IIc, in the right amateur spirit operators should take notice of these agreements which are made for operating convenience, but no right to reserved frequencies can be derived from a mention in the Usage column or from the following notes (except where Aexclusive@is mentioned@).

2.1. Footnotes

f. The HB/DL/OE wide-shift repeater system, already in use for a long time, is valuable with a view to a better utilisation of the whole band. Hence IARU Region 1 endorses the system.
This also applies for the French repeater channel system, also adopted by the Netherlands and Belgium, which IARU Region 1 supports as a useful measure to fill a hitherto unused part of the band.
For the numbering of FM telephony channels see 4.1

g. In the Usage section of the 435 MHz bandplan the following frequency segments have been designated for digital communications:

- i) 430.544 - 430.931 MHz Extension of the 7.6 MHz repeater system input for digital comm.
438.194 - 438.531 MHz Output channels for the above
- ii) 433.619 - 433.781 MHz
438.019 - 438.181 MHz
- iii) 430.394 - 430.581 MHz For digital communication links
439.794 - 439.981 MHz For digital communication links

With due regard to the band allocated to the Amateur Service by the national Administration, the interests of other users, possible interference from e.g. ISM, the specific digital technique or system to be accommodated etc., a sub-regional, or national choice may be made within the above segments.

h. In those countries where 433.619 - 433.781 MHz is the only segment of the 435 MHz band available for digital communications, modulation techniques requiring a channel separation exceeding 25 kHz should not be used. If different or incompatible use of this part of the frequency spectrum is contemplated in neighbouring countries, this use should be coordinated between the countries concerned with the aim of avoiding harmful interference.

i. On a temporary basis, in those countries where 433.619 - 433.781 MHz is the only segment of the 435 MHz band available for Digital Communications:

- 1. Channels with centre frequencies 432.500, 432.525, 432.550, 432.575, 434.450, 434.475, 434.500, 434.525, 434.550 and 434.575 may be used for digital communications.
- 2. Use of these channels must not interfere with linear transponders.
- 3. Modulation techniques requiring a channel separation exceeding 25 kHz must not be used on these channels. (De Haan, 1993)

j. At the IARU Region 1 Conference in Torremolinos (1990) the following recommendation was adopted regarding the segments for repeaters and links, shown in footnote g:

For a repeater/link to be installed within 150 km of a national border, the member society should co-ordinate the frequency allocation and the technical (system) data with the member societies in neighbouring countries. Special attention should be paid to the common good practice of using directional antennas and the minimum power necessary.

As a matter of course this agreement is also valid for any link experiments carried out on the multi-mode channels in the segment 438.544--438.631 MHz. (De Haan, 1993).

- k. These multi-mode channels are to be used for experimenting with new transmission technologies (De Haan, 1993)
- l. In the United Kingdom the use of low-power speech repeaters on repeater channels in the segment 438.419--438.581 is allowed. Where necessary, frequencies will be coordinated with neighbouring countries (De Haan, 1993).
- m. Experiments using wide band digital modes may take place in the 435 MHz band in those countries that have the full 10 MHz allocation. These experiments should be in the all modes section around a frequency of 434 MHz, use horizontal polarisation and the minimum power required.(Tel Aviv 1996)
- n. Common frequencies for Simplex (FM) Internet voice gateways are:
433.950, 433.9625, 433.975, 433.9875, 434.0125, 434.434.025, 434.0375, 434.050 MHz
(Cavtat 2008)
- o. All Voice repeater channels may use FM or Digital Voice modes. (Cavtat 2008)

4.6 1240 - 1300 MHz BANDPLAN

Frequency MHz	Maximum Bandwidth	MODE	USAGE
1240.000 1240.500	2700 Hz	ALL MODE	(reserved for future)
1240.500 1240.750	500Hz	Telegraphy MGM	Beacons (reserved for future)
1240.750 1241.000	12kHz	FM Digital voice	(reserved for future)

1240.000 1243.250	20kHz	ALL MODE	1240.000-1241.000 Digital communications 1242.025-1242.250 Repeater output, ch. RS1 - RS10 1242.275-1242.700 Repeater output, ch. RS11 - RS28 1242.725-1243.250 Packet radio duplex, ch. RS29 - RS50
1243.250 1260.000	(d)	ATV Digital ATV	1258.150-1259.350 Repeater output, ch. R20 - R68
1260.000 1270.000	(d)	Satellite Service	
1270.000 1272.000	20kHz	All Mode	1270.025-1270.700 Repeater input, ch. RS1 -- RS28 1270.725-1271.250 Packet Radio duplex, ch. RS29 -- RS50
1272.000 1290.994	(d)	ATV Digital ATV	
1290.994 1291.481	12kHz	FM Digital voice Repeater INPUT	RM0 (1291.000) -- RM19 25kHz spacing RM19 (1291.475)
1291.481 1296.000	(d)	ALL MODES	1293.150-1294.350 Repeater input, R20 (1293.150) R68 (1294.350)

Frequency MHz	Maximum Bandwidth	MODE	USAGE
1296.000 1296.150	500Hz	Telegraphy MGM	1296.00-1296.025 1296.138 Moonbounce PSK31 centre of activity
1296.150 1296.800	2700Hz	Telegraphy SSB MGM	1296.200 1296.370 1296.400-1296.600 1296.500 1296.600 Narrow-band centre of activity FKS441 MS calling Linear transponder input Image center (SSTV, Fax etc) Narrowband Data center (MGM, RTTY,...) 1296.600-1296.700 1296.750-1296.800 Linear transponder output Local Beacon (10W ERP max)
1296.800 1296.994	500Hz	Telegraphy MGM	Beacons exclusive (b)
1296.994 1297.481	12kHz	FM Digital voice Repeater OUTPUT	RM0 (1297.000) 25 KHz spacing RM19 (1297.475)
1297.494 1297.981	12kHz	FM (c) Digital Voice (e)	SM20 (1297.500) (25 KHz spacing - SIMPLEX) 1297.500 FM center of activity 1297.725 Digital Voice calling (25 KHz spacing - SIMPLEX) 1297.900-1297.975 Simplex FM Internet voice gateways SM39 (1297.975)
1298.000 1300.000	20kHz	All Modes	1298.025-1298.500 1298.500-1300.000 1298.725-1299.000 Repeater output channel freqs, ch. RS1 -- RS28 Digital communications (within RS channels) d) Packet-Radio duplex channel freqs, ch. RS29 -- RS40

NOTES ON THE 1240 - 1300 MHz BANDPLAN

1. IARU REGION 1 BANDPLAN

The following notes are part of the IARU Region 1 bandplan for this band, originally adopted during the IARU Region 1 Conference at Noordwijkerhout (1987), and all member societies should strongly promote adherence to the recommendations made in these notes.

At the IARU Region-1 Conference at Cavtat (2008), Recommendation CT08_C5_27 was adopted which designated the 1240.0-1240.75MHz segment as an alternative narrowband section and makes a series of recommendations for replanning other parts of the band for DATV and Digital Voice & Data

1.1. Footnotes

- a. deleted
- b. Refer to Beacons Chapter for coordination of beacons in the beacon sub-band Section 11
- c. In countries where 1298 - 1300 MHz is not allocated to the Amateur Service (e.g. Italy) the FM simplex segment may also be used for digital communications.
- d. Bandwidth limits according to national regulations.
- e. This segment is for simplex use only with no Digital Voice gateways. Embedded data traffic is allowed along with digital voice. Digital Voice users should check that the channel is not in use by other modes

2. USAGE

The following note refers to the Usage column in the bandplan. As already set out in the introduction to section IIc, in the right amateur spirit operators should take notice of these agreements which are made for operating convenience, but no right to reserved frequencies can be derived from a mention in the Usage column.

2.1. General

During contests and bandopenings local traffic using narrow-band modes should operate between 1296.500 - 1296.800 MHz.

4.7 2300 -2450 MHz BANDPLAN

Frequency	Mode	Usage
2300.000 SUB-REGIONAL (national) BANDPLANNING (a) 2320.000		2304 - 2306 Narrow band segment in countries where the 2320-2322 segment is not available 2308 - 2310 Narrow band segment in HB
2320.000 2320.150	TELEGRAPHY EXCLUSIVE (c)	2320.000-2320.025 EME 2320.138 PSK31 centre of activity
2320.150 2320.800	TELEGRAPHY/ SSB (c)	2320.200 SSB centre of activity 2320.750-2320.800 Local Beacons (10W ERP max)
2320.800 2321.000	BEACONS EXCLUSIVE (c)	
2321.000 2322.000	FM & DIGITAL VOICE SIMPLEX & REPEATERS (b)	
2322.000 2400.000	All Modes (b)	2322.000-2355.000 ATV 2355.000-2365.000 Digital communications 2365.000-2370.000 Repeaters 2370.000-2392.000 ATV 2392.000-2400.000 Digital communications
2400.000 2450.000	Amateur Satellite Service	2427.00 - 2443.00 ATV if no satellite uses this segment

NOTES ON THE 2300 - 2450 MHz BANDPLAN

- a) The words "Sub-regional (national) bandplanning" appearing in IARU Region 1 VHF/UHF/Microwave bandplans mean the following:

In bands and sub-bands not available throughout Region 1, band-planning should be coordinated on a sub-regional basis between the countries where those bands and sub-bands are allocated to the Amateur Service. The words "national bandplanning" refer to bands which are available only in a single country (such as the 70 MHz band allocation), or only in a few widely separated countries.

(Torremolinos 1990)

- b) In countries where the ALL MODES segment 2322 - 2400 MHz is not allocated to the Amateur Service, the FM SIMPLEX & REPEATER segment 2321 - 2322 MHz may be used for digital data transmissions.
For the specification of FM see section VIb
- c) In countries where the narrow-band segment 2320 - 2322 MHz is not available, the following alternative narrow-band segments can be used:

2304 - 2306 MHz

2308 - 2310 MHz

- c) Refer to Beacons Chapter for coordination of beacons in the beacon sub-band
Section **Fehler! Verweisquelle konnte nicht gefunden werden.**

4.8 3400 -3475 MHz BANDPLAN

IARU Region 1 bandplan		Usage	
3400.000 NARROW-BAND MODES		3400.100	Center of activity and EME
		3400.750-3400.800	Local Beacon (e)
3400.800			
3400.800	BEACONS ONLY d)		
3400.995			
3401.000	NARROW-BAND MODES		
3402.000			
3402.000	SATELLITE DOWNLINKS a)c) ALL MODES		
3410.000			
3410.000	ALL MODES	3420.000-3430.000	Digital Communications
		3450.000-3455.000	Digital Communications
3475.000			

NOTES ON THE 3400 – 3475 MHz BANDPLAN

- a) CEPT Footnote EU17 permits Amateur Service in 3400-3410MHz
- b) EME Centre of Activity has migrated from 3456 to 3400.1MHz to promote harmonised usage and activity
- c) Amateur Satellite Service is allocated in 3400-3410MHz in Regions 2&3 and in some countries of Region-1.
- d) 3400.750-3400.800MHz may be designated for Local Beacon use (10W ERP max) by National Societies.
- e) Refer to Beacons Chapter for coordination of beacons in the beacon sub-band

References

Vienna-2007 C5 Paper-B13: Allocations at 3400MHz
 Cavtat-2008 Paper CT08_C5_17: 3400MHz Amateur Satellite Allocation
 Cavtat-2008 Paper CT08_C5_18: 3400MHz EME developments
 Cavtat-2008 Paper CT08_C5_25: Microwave Beacon Bands

4.9 5650 - 5850 MHz BANDPLAN

IARU Region 1 bandplan		Usage	
5650.000	AMATEUR SATELLITE SERVICE (up-link)		
5668.000			
5668.000	AMATEUR SATELLITE SERVICE (up-link) & NARROW BAND MODES (a)	5668.200	Narrow band center of activity
5670.000			
5670.000	DIGITAL		
5700.000			
5700.000	ATV		
5720.000			
5720.000	ALL MODES		
5760.000	NARROW BAND MODES (a)	5760.200	Narrow band center of activity
5760.800		5760.750-5760.800	Local Beacon (d)
5760.800	BEACONS ONLY		
5760.990			
5761.000	NARROW BAND MODES (a)		
5762.000			
5762.000	ALL MODES		
5790.000			
5790.000	AMATEUR SATELLITE SERVICE (down-link)		
5850.000			

NOTES ON THE 5650 - 5850 MHz BANDPLAN

Footnotes

- a) Societies are urged to inform their members that stations should preferably be able to operate in both narrow-band segments.
- b) 5760.750-5760.800MHz may be designated for Local Beacon use (10W ERP max) by National Societies.
- d) Refer to Beacons Chapter for coordination of beacons in the beacon sub-band Section 11.

4.10 10.000 - 10.500 GHz BANDPLAN

IARU Region 1 bandplan		Usage	
10.000	DIGITAL		
10.150			
10.150	ALL MODES		
10.250			
10.250	DIGITAL		
10.350			
10.350	ALL MODES		
10.368			
10.368	NARROW BAND MODES	10.3682	Narrow band center of activity
10368.800		10368.750-10368.800	Local Beacon (d)
10.368.800	BEACONS ONLY (c)		
10.368.990			
10.369	NARROW BAND MODES		
10.370			
10.370	ALL MODES		
10.450			
10.450	AMATEUR SATELLITE SERVICE & ALL MODES	10.450-10.452	Narrow band modes in countries where 10.368-10.370 is not available
10.500			

NOTES ON THE 10.0 - 10.5 GHz BANDPLAN

1. Footnotes

- a) In those countries where the narrow-band segment 10368 - 10370 MHz is not available, the segment 10450 - 10452 MHz is suggested as an alternative narrow-bandwidth segment.
- b) 10368.750-10368.800 may be designated for Local Beacon use (10W ERP max) by National Societies.
- d) Refer to Beacons Chapter for coordination of beacons in the beacon sub-band Section 11

4.11 24.000 - 24.250 GHz BANDPLAN (San Marino 2002)

IARU Region 1 bandplan	Usage
24.000 ALL MODES	
24.048 24.048 AMATEUR SATELLITE SERVICE & NARROW BAND MODES	24.0482 Narrow band center of activity 24048.750-24049.800MHz Local Beacon (b)
24.048.800 24.048.800 BEACONS (d)	
24.048.995 24.049 AMATEUR SATELLITE SERVICE & NARROW BAND MODES	
24.050 24.050 ALL MODES (not preferred) (a)	24.125 Preferred operating frequency for wide-band equipment
24.250	

1. Footnotes

- a) In the lower 50 MHz of the 24 GHz band the amateur and amateur satellite service have a primary/exclusive status, while the status is secondary in the upper 200 MHz . The all mode section in the secondary segment should only be used in case the preferred segment cannot be used.
- b) 24048.750-24049.800MHz may be designated for Local Beacon use (10W ERP max) by National Societies.
- d) Refer to Beacons Chapter for coordination of beacons in the beacon sub-band

4.12 47.000 - 47.200 GHz BANDPLAN (Vienna 2004)

IARU Region 1 bandplan	Usage
<p>47.000</p> <p>ALL MODES</p> <p>47.088</p>	
<p>47.088</p> <p>AMATEUR SATELLITE SERVICE & NARROW BAND MODES</p> <p>47.090</p> <p>47.090</p> <p>ALL MODES</p> <p>47.200</p>	<p>47.088200 Narrow band center of activity</p>

4.13 75.50-81.50 GHz BANDPLAN (Davos 2005)

IARU Region 1 bandplan	Usage
75.500 AMATEUR SATELLITE SERVICE & ALL MODES (Preferred [1]) 76.000	75976.200 MHz : Preferred Narrow band centre of activity
76.000 ALL MODES (not preferred) [2] 77.500	76032.200 MHz :Narrow Band Centre of activity in some countries
77.500 AMATEUR SATELLITE SERVICE & NARROW BAND MODES (non-preferred / preferred)[3] 77.501	77500.200 MHz: Preferred NB centre of activity in countries outside the CEPT area
77.501 ALL MODES (Preferred segment) 78.000	
78.000 ALL MODES (not preferred) 81.500	

Footnotes

1. Preferred in those CEPT countries having implemented EU35.
2. Between 77.5 and 78 GHz the amateur and amateur satellite service have a primary/exclusive status and between 75,5-76 GHz a primary status through ECA footnote EU35 in CEPT countries, while the status is secondary in the remainder of the allocation. The all mode section in the secondary segment should only be used in case the preferred segment cannot be used
3. Preferred in those countries not having implemented EU35

4.14 122.25 - 123 GHz Bandplan (San Marino 2002)

IARU Region 1 bandplan	Usage
122.250 NARROW BAND MODES 122.251	
122.251 ALL MODES 123.000	

4.15 134 - 141 GHz BANDPLAN (San Marino 2002)

IARU Region 1 bandplan	Usage
134.000 AMATEUR SATELLITE SERVICE & NARROW BAND MODES 134.001	
134.001 ALL MODES (Preferred segment) 136.000	
136.000 ALL MODES (not preferred) (a) 141.000	

1. Footnotes

a. Between 134 and 136 GHz the amateur and amateur satellite service have a primary/exclusive status, while the status is secondary in the remainder of the allocation. The all mode section in the secondary segment should only be used in case the preferred segment cannot be used

4.16 241 - 250 GHz BANDPLAN (San Marino 2002)

IARU Region 1 bandplan	Usage
<p>241.000</p> <p>ALL MODES (not preferred) (a)</p> <p>248.000</p>	
<p>248.000</p> <p>AMATEUR SATELLITE SERVICE & NARROW BAND MODES</p> <p>248.001</p>	
<p>248.001</p> <p>ALL MODES (Preferred segment)</p> <p>250.000</p>	

Footnotes

a. Between 248 and 250 GHz the amateur and amateur satellite service have a primary/exclusive status, while the status is secondary in the remainder of the allocation. The all mode section in the secondary segment should only be used in case the preferred segment cannot be used